

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/030327 A1

(51) International Patent Classification⁷: **A61N 1/39**

(21) International Application Number:
PCT/IB2004/051707

(22) International Filing Date:
7 September 2004 (07.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/507,156 30 September 2003 (30.09.2003) US

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS, N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **JONSEN, Eric**
[US/US]; P.O. Box 3003, Bothell, WA 98041-3003 (US).

(74) Common Representative: **KONINKLIJKE PHILIPS ELECTRONICS, N.V.**; c/o W. Brinton Yorks, Jr., P.O. Box 3003, Bothell, WA 98041-3003 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IDENTIFICATION SYSTEM FOR DEFIBRILLATOR ELECTRODE PACKAGE

10



(57) Abstract: An automatic external defibrillator electrode package (10; 20; 30) includes a coded conductive label (13; 23; 33) that uniquely identifies the type of automatic electrode contained therein. Pins (42a-d) on the defibrillator body (40) make electrical contact with the conductive label (13; 23; 33) when the package (10; 20; 30) is attached to the defibrillator (50). These pins (42a-d) sense the shape of the conductive label (13; 23; 33) to ascertain the electrode type, thereby enabling the AED (50) to automatically set the proper operating mode.

WO 2005/030327 A1

**Declaration under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE,

IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

IDENTIFICATION SYSTEM FOR DEFIBRILLATOR ELECTRODE PACKAGE

The present invention relates generally to automatic external defibrillators, and more
5 particularly to a method and apparatus for attaching electrodes in an automatic external
defibrillator.

Present automatic external defibrillators (AEDs) must adapt their operation to the
mode of use. For example, an AED may be used to defibrillate an adult or an infant, each of
which requires a different treatment protocol. Moreover, an AED may also be used in a
10 training mode or strictly in a multi-electrode monitoring mode, in which case no defibrillation
energy should be discharged through the electrodes. Thus, an AED must employ some
technique for determining the operating mode.

There are a number of ways that present AEDs switch operating modes. One way is
via a manual switch. A user of the AED simply changes a switch setting to the proper mode.
15 Manual switching represents a suboptimal solution because setting a manual switch requires a
user who may be employing the AED in a cardiac emergency to perform an extra and
potentially confusing step to ensure the AED is in the proper rescue mode. Placing the AED
in the wrong operating mode can have fatal consequences in certain situations.

Another technique employed by existing AEDs uses a different plug for each type of
20 electrode. In this case, the AED merely senses which electrode is in use. This solution is
impractical because it adds complexity to a device that must be simple, small, inexpensive
and lightweight.

One method of automatically identifying the type of connected electrode is described
in U.S. Patent No. 6,560,485 to Herleikson and assigned to the same assignee, which patent is
25 entitled "Four Contact Identification Defibrillator Electrode System." This patent describes

segmented male and female plugs that selectively short together the segments when the plugs are mated. This patent is hereby incorporated by reference as if repeated herein in its entirety, including the drawings.

The present invention is therefore directed to the problem of developing a method and
5 apparatus for enabling activation of the proper operating mode for an automatic external defibrillator that does not increase the size, weight or complexity of the automatic external defibrillator.

The present invention solves these and other problems by providing an automatic external defibrillator electrode package that comprises a coded conductive label that uniquely
10 identifies the type of automatic electrode contained therein. Pins on the defibrillator body make electrical contact with the metallic label when the package is attached to the defibrillator. These pins sense the shape of the conductive label to ascertain the electrode type, thereby enabling the AED to automatically set the proper operating mode.

According to one aspect of the present invention, an exemplary embodiment of a
15 method for identifying an electrode type in an automatic external defibrillator includes providing a shaped conductive label on an automatic external defibrillator electrode package that uniquely identifies a type of electrode contained therein and coupling one or more pins to the shaped conductive label when the automatic external defibrillator electrode package is coupled to the defibrillator. In this embodiment, a shape of the shaped conductive label can
20 be sensed with the one or more pins to ascertain the type of electrode contained therein and an operating mode for the automatic external defibrillator can be selected based on the shape of the shaped conductive label.

According to another aspect of the present invention, an electrode package for an automatic external defibrillator includes a cartridge and a shaped metallic label. The
25 cartridge contains one or more electrodes of a particular type. The shaped metallic label is

disposed on the cartridge and uniquely identifies the particular type of electrode contained therein via its shape.

According to still another aspect of the present invention, an automatic external defibrillator includes one or more electrode cartridges and one or more shaped metallic labels. Each of the one or more electrode cartridges contains one or more electrodes of a particular type. Each of the one or more shaped metallic labels is disposed on one of the one or more electrode cartridges and each uniquely identifies a particular type of electrode contained therein based on its shape. This embodiment can include an electrode cartridge receptacle to accept each of the one or more electrode cartridges. The electrode cartridge receptacle includes one or more sensing pins to couple in a unique pattern to the one or more shaped metallic labels when each of the one or more electrode cartridges is inserted into the electrode cartridge receptacle. Moreover, this embodiment can include a processor establishing a mode of operation of the automatic external defibrillator based on the particular one of the one or more shaped metallic labels sensed by the one or more sensing pins.

FIG 1 illustrates an exemplary embodiment of an electrode package according to one aspect of the present invention.

FIG 2 illustrates another exemplary embodiment of an electrode package according to another aspect of the present invention.

FIG 3 illustrates another exemplary embodiment of an electrode package according to yet another aspect of the present invention.

FIG 4 illustrates an exemplary embodiment of an electrode receptacle for accepting one of the exemplary embodiments in FIGs 1-3 according to still another aspect of the present invention.

FIG 5 depicts a block diagram of an exemplary embodiment of an automatic external defibrillator according to still another aspect of the present invention.

FIG 6 depicts a flow chart of an exemplary embodiment of a method for identifying a type of electrode package in an automatic external defibrillator according to yet another aspect of the present invention.

It is worthy to note that any reference herein to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

In the embodiment 10 illustrated in FIG 1, a shaped conductive label 13 having two portions 13a, 13b is disposed in the back of a rigid electrode cartridge 10. Contacts 11 and 12 are the power contacts through which the current or ECG signals flow when the electrodes are in use (of course, assuming the mode of operation requires current or ECG signal). The electrodes (not shown) are stored within the cartridge 10 and connect through the cartridge wall to the defibrillator (not shown). The electrode connections 11, 12 are separate from the conductive label 13.

Installation of the cartridge 10 into the defibrillator cartridge receptacle (see element 40, FIG 4) places the portions 13a, 13b of the conductive label 13 in electrical contact with four spring-loaded pins (see element 42, FIG 4) projecting from the receptacle 40. In this embodiment 40, the top two pins 42b, 42d contact the portion 13b of conductive label 13, and the bottom two pins 42a, 42c contact the portion 13a of conductive label 13. Thus, conductive label portion 13a electrically shorts pin 42a to pin 42c, and conductive label portion 13b shorts pin 42b to pin 42d. The AED senses the resultant combination of electrical shorts and matches the sensed combination to a known cartridge type. In general,

the shape of the conductive label 13 can be altered such that some or all of the pins 42a-d are shorted together in a unique combination to connote the type of electrode cartridge 10 to which the conductive label 13 is applied. The sensing pins (42a-d) are disposed to couple in a unique pattern to two or more portions of each of the shaped metallic labels to redundantly
5 identify the particular type of electrode.

The conductive label 13 is preferably a material that will not erode under vibration or corrode over time. Erosion or corrosion could cause the sensed label shape to change, by opening what was otherwise an intended electrical short path. Therefore, the preferred label material is a gold-plated metal foil. Alternatively, the label could be comprised of a
10 metallized printed circuit board or of a solid metal plaque.

In addition, the defibrillator sensing pins 42 should be held under elastic compression against the label 13, when the cartridge 10, 20, 30 is installed. Such a disposition reduces erosive wear under vibration or shock, while maintaining a secure electrical connection. The compression device should be set low enough to prevent damage to the pins 42 during use.
15 An exemplary embodiment of the elastic compression device includes a spring-loaded pin. Alternatively, the elastic compression device may be disposed between conductive label 13 and the electrode cartridge body, such that the conductive label 13 is held under elastic compression against fixed pins 42.

The unique combination of connected pins 42, sensed by the defibrillator, indicates
20 the type of electrode cartridge 10, 20, 30 installed. For example, a conductive label 13 for an adult electrode cartridge 10 may be a square with four quadrants, pairs of which are electrically conductive as shown in FIG 1. Thus, pairs of sensing pins 42a-c and 42b-d are shorted. Certainly, this shape could be used for other types of electrodes (but not at the same time, of course), as long as the shape is uniquely matched to the type of electrode.

Turning to FIG 2, shown therein is an exemplary embodiment 20 of another type of electrode cartridge. This can be used, for example, for a pediatric electrode cartridge. In this case, the conductive label 23 has two portions 23a, 23b that are rotated about 90 degrees relative to the conductive label 13 of FIG 1. Thus, pins 42a and 42b contact portion 23a of conductive label 23 while pins 42b and 42c contact portion 23b of conductive label 23. This provides another unique combination of sensing pins to determine the type of electrode cartridge automatically.

Turning to FIG 3, shown therein is an exemplary embodiment 30 of another type of electrode cartridge. This can be used, for example, for a training electrode cartridge. In this case, the conductive label 33 has a single portion. Thus, pins 42a, 42c and 42d contact conductive label 33 while pin 42b remains isolated. This provides another unique combination of sensing pins to determine the type of electrode cartridge automatically.

Turning to FIG 5, shown therein is a block diagram of an exemplary embodiment of an automatic external defibrillator. In this embodiment 50, a processor 51 establishes the mode of operation of the AED. The sensing pins 52 are coupled to the processor 51 and in combination sense a unique shape of a shaped or coded conductive label 53 that is disposed on each of the electrode packages.

Each electrode package for an automatic external defibrillator includes a cartridge for containing electrodes of a particular type and a shaped conductive label disposed on the cartridge. The shaped conductive label uniquely identifies the particular type of electrode contained therein via its shape.

The AED also includes an electrode cartridge receptacle to accept each of the electrode cartridges. The electrode cartridge receptacle includes one or more sensing pins to couple in a unique pattern to each of the shaped conductive labels when the electrode cartridge is inserted into the electrode cartridge receptacle.

The processor establishes a mode of operation of the automatic external defibrillator based on the particular shaped conductive label sensed by the one or more sensing pins. In a preferred embodiment, each of the sensing pins is spring-loaded to maintain the sensing pin in electrical contact with a portion of the shaped conductive label when the electrode cartridge is inserted into the electrode cartridge receptacle.

Each of the automatic external defibrillator electrode cartridges includes two contacts for interfacing the patient electrodes contained therein to the defibrillator and the automatic external defibrillator electrode cartridge receptacle includes two opposing contacts which mate with the two contacts on each of the automatic external defibrillator electrode cartridges. The two contacts on the automatic external defibrillator electrode cartridge receptacle are different than the sensing pins.

Other shapes than those shown herein will cause different combinations of the four sensing pins to be shorted or opened. There can be more sensing pins than four, as well as less sensing pins than four.

Turning to FIG 6, shown therein is an exemplary embodiment of a method 60 for identifying an electrode package in an AED and for operating the AED accordingly.

In step 61, a shaped conductive label is provided on an automatic external defibrillator electrode package that uniquely identifies a type of electrode contained therein. The shaped conductive label can be square, half-moon shaped, or any other unique shape for each type of electrode package that results in different combination of pins contacting the shaped conductive label.

In step 62, one or more pins are coupled to the shaped conductive label when the automatic external defibrillator electrode package is coupled to the defibrillator. Different combinations of pins will contact the shaped conductive label for different electrode types.

In step 63, the shape of the shaped conductive label is sensed with the one or more pins to ascertain the type of electrode contained therein. This can be accomplished by redundantly sensing two or more portions of the shape of the shaped conductive label with two or more pins to ascertain the type of electrode contained therein.

5 In step 64, an operating mode for the automatic external defibrillator is selected based on the shape of the shaped conductive label sensed by the combination of the pins. For example, if all four pins are contacted (shorted or opened), then one mode of operation is selected, whereas if only three pins are contacted (shorted or opened), another mode is selected.

10 There are a number of advantages to the present invention. First, because the electrode type identification system is separate from the defibrillation energy connector, a potential mis-identification due to an incorrectly installed or dislodged connector is eliminated. Second, the defibrillator identification pins and the conductive label can be disposed for identification redundancy. For example, referring to the electrode cartridge 10 of FIG 1 and the defibrillator pins 42a-d in FIG 4, the defibrillator can be configured to positively identify the cartridge type based on detecting either of the shorted pin pairs 42b-d or 42a-c. In this embodiment, one broken pin or contact blocked by debris in one pin pair will not confuse the defibrillator because the other pin pair will be shorted and detected normally.

20 Not only can the conductive label be fabricated inexpensively, but also the label orientation by itself can connote a specific electrode type. Thus, a single label design can denote two or more cartridge types. FIGs 1-3 illustrate one embodiment of the conductive label, although the label of an exemplary embodiment could be fabricated or applied under different orientations to identify at least twelve different electrode types.

Additionally, the label can be uniquely coded to indicate the type of electrode, which code is sensed by the electrode cartridge receptacle. For example, a bar code could be employed as a unique label.

Although various embodiments are specifically illustrated and described herein, it will be appreciated that modifications and variations of the invention are covered by the above teachings and are within the purview of the appended claims without departing from the spirit and intended scope of the invention. For example, specific shapes for the conductive labels are depicted herein, yet other shapes are possible without departing from the scope of the present invention. Substitute contact elements that function similarly to pins will be obvious to one of ordinary skill in the art. Moreover, while four pins are shown, other numbers of pins can be used without departing from the scope of the present invention. Furthermore, these examples should not be interpreted to limit the modifications and variations of the invention covered by the claims but are merely illustrative of possible variations.

CLAIMS:

1. A method (60) for identifying an electrode type in an automatic external defibrillator (50) comprising the steps of:

providing (61) a shaped conductive label (13; 23; 33) on an automatic external defibrillator electrode package (10; 20, 30) that uniquely identifies a type of electrode contained therein; and

coupling (62) one or more pins (42a-d) to the shaped conductive label (13; 23; 33) when the automatic external defibrillator electrode package (10; 20; 30) is coupled to the defibrillator (50).

2. The method according to claim 1, further comprising the step of:

sensing (63) a shape of the shaped conductive label (13; 23; 33) with the one or more pins (42a-d) to ascertain the type of electrode contained therein.

3. The method according to claim 1, further comprising the step of:

selecting (64) an operating mode for the automatic external defibrillator (50) based on the shape of the shaped conductive label (13; 23; 33).

4. The method (60) according to claim 2, wherein said sensing step further comprises redundantly sensing two or more portions of said shape of the shaped conductive label (13; 23; 33) with two or more pins to ascertain the type of electrode contained therein.

5. An electrode package (10; 20; 30) for an automatic external defibrillator (50) comprising:

a cartridge (10; 20; 30) for containing one or more electrodes of a particular type; and

a shaped conductive label (13; 23; 33) disposed on the cartridge (10; 20; 30), said shaped conductive label (13; 23; 33) uniquely identifying the particular type of electrode contained therein via the shape of said shaped label (13; 23; 33).

6. An automatic external defibrillator (50) comprising:

one or more electrode cartridges (10; 20; 30), each containing one or more electrodes of a particular type; and

one or more shaped conductive labels (13; 23; 33), each disposed on one of the one or more electrode cartridges (10; 20; 30), each of said one or more shaped conductive labels (13; 23; 33) uniquely identifying a particular type of electrode contained therein based on the shape of said shaped label (13; 23; 33).

7. The automatic external defibrillator (50) according to claim 6, further comprising:

an electrode cartridge receptacle (40) to accept each of the one or more electrode cartridges (10; 20; 30), said electrode cartridge receptacle (40) including one or more sensing pins (42a-d) to couple in a unique pattern to the one or more shaped conductive labels (13; 23; 33) when each of the one or more electrode cartridges (10; 20; 30) is inserted into the electrode cartridge receptacle (40).

8. The automatic external defibrillator (50) according to claim 7, wherein said sensing pins (42a-d) are disposed to couple in a unique pattern to two or more portions of each of said shaped conductive labels (13; 23; 33) to redundantly identify said particular type of electrode.

9. The automatic external defibrillator (50) according to claim 7, further comprising:
a processor (51) establishing a mode of operation of the automatic external defibrillator (50) based on the particular one of the one or more shaped conductive labels (13; 23; 33; 53) sensed by the one or more sensing pins (42a-d).

10. The automatic external defibrillator (50) according to claim 7, wherein each of the one or more sensing pins (42a-d) comprises a spring-loaded pin to maintain said each sensing pin in electrical contact with the one or more shaped conductive labels (13; 23; 33; 53) when each of the one or more electrode cartridges (10; 20; 30) is inserted into the electrode cartridge receptacle (40).

11. The automatic external defibrillator (50) according to claim 7, wherein each of the one or more shaped conductive labels (13; 23; 33; 53) comprises a gold-plated metal.

12. The automatic external defibrillator (50) according to claim 9, wherein each of the one or more shaped conductive labels (13; 23; 33; 53) comprises a unique shape.

13. The automatic external defibrillator (50) according to claim 12, wherein the one or more sensing pins (42a-d) sense the unique shape of the one or more shaped conductive labels (13; 23; 33; 53) when each of the one or more electrode cartridges (10; 20; 30) is inserted into the electrode cartridge receptacle (40).

14. The automatic external defibrillator (50) according to claim 13, wherein the processor (51) establishes a mode of operation of the automatic external defibrillator (50) based on the sensed shape of the conductive label (13; 23; 33; 53).

15. The automatic external defibrillator (50) according to claim 7, wherein each of the automatic external defibrillator electrode cartridges (10; 20; 30) includes two contacts (11, 12) for electrically connecting patient electrodes to the automatic external defibrillator (50) and the automatic external defibrillator electrode cartridge receptacle (40) includes two contacts (41, 43) for electrically connecting the automatic external defibrillator to the two contacts (11, 12) on each of the automatic external defibrillator electrode cartridges (10; 20; 30), and said two contacts (41, 43) on the automatic external defibrillator electrode cartridge receptacle (40) are different than said one or more sensing pins (42a-d).

16. A method (60) for identifying an electrode type in an automatic external defibrillator (50) comprising the steps of:

providing (61) a first conductive label (13; 23; 33) on a first type of an automatic external defibrillator electrode package (10; 20; 30), said first conductive label (13; 23;

33) having a first shape that uniquely identifies a type of electrode contained therein; and

providing (61) a second conductive label (13; 23; 33) on a second type of an automatic external defibrillator electrode package (10; 20; 30), said second conductive label (13; 23; 33) having a second shape that uniquely identifies a type of electrode contained therein.

17. The method (60) according to claim 16, further comprising the step of:

coupling (62) one or more pins to the first or second conductive label (13; 23; 33) when the automatic external defibrillator electrode package (10; 20; 30) on which the first or

second conductive label (13; 23; 33), respectively, is disposed is coupled to the defibrillator (50).

18. The method (60) according to claim 17, wherein the one or more pins (42a-d) comprise one or more spring-loaded pins.

19. The method (60) according to claim 17, further comprising the step of:
sensing (63) a shape of the shaped conductive label (13; 23; 33) with the one or more pins to ascertain a type of electrode contained therein.

20. The method (60) according to claim 16, further comprising the step of:
selecting (64) an operating mode for the automatic external defibrillator (50) based on the shape of the first and second shaped conductive labels (13; 23; 33).




FIG. 1

10




FIG. 2




FIG. 3




FIG. 4


50

FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

IB2004/051707

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61N1/39

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 A61N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 951 598 A (HARRIS JOHN F ET AL) 14 September 1999 (1999-09-14) column 2, line 23 - column 3, line 11 -----	1-20
A	US 6 560 485 B2 (HERLEIKSON EARL CLARK) 6 May 2003 (2003-05-06) cited in the application paragraph '0043! -----	1-20
A	WO 03/020362 A (ACCESS CARDIOSYSTEMS INC) 13 March 2003 (2003-03-13) page 47, lines 8-13 -----	1-20
A	US 6 125 298 A (GILMAN BYRON L ET AL) 26 September 2000 (2000-09-26) column 10, lines 4-8 -----	1-20



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

13 January 2005

Date of mailing of the international search report

27/01/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Aronsson, F

INTERNATIONAL SEARCH REPORT

IB2004/051707

Patent document cited in search report		Publication date	Patent family member(s)			Publication date
US 5951598	A	14-09-1999	NONE			
<hr/>						
US 6560485	B2	03-10-2002	US	2002143366 A1		03-10-2002
			CN	1460030 T		03-12-2003
			EP	1372784 A2		02-01-2004
			WO	02076549 A2		03-10-2002
			JP	2004534566 T		18-11-2004
<hr/>						
WO 03020362	A	13-03-2003	CA	2459049 A1		13-03-2003
			EP	1432474 A2		30-06-2004
			WO	03020362 A2		13-03-2003
			US	2003167075 A1		04-09-2003
<hr/>						
US 6125298	A	26-09-2000	NONE			
<hr/>						